



## CLEANING AND CARE



### SPRAY CLEANER

#### RECOMMENDED USE

Osmo Spray Cleaner is especially suitable for the cleaning and maintenance of oiled and waxed wood surfaces in indoor areas. It is particularly recommended for surfaces treated with Osmo TopOil.

#### MANUAL PROCESSING

1. Remove dirt and debris.
2. Spray onto surface.
3. Clean the surface subsequently with a lint-free cotton cloth and rub dry.

#### ADVANTAGES

- > Highly effective cleaning
- > Cleans without damaging the surface
- > Preserves and restores the surface
- > Easy application
- > Suitable for household and commercial use
- > Suitable for all wood species



Apply with:



Osmo Holz und Color  
GmbH & Co. KG

Affhüppen Esch 12  
D-48231 Warendorf

PO Box 110161  
D-48203 Warendorf

Telephone +49 (0)2581/922-100  
Telefax +49 (0)2581/922-200

[www.osmo.de/en](http://www.osmo.de/en)  
[info@osmo.de](mailto:info@osmo.de)



© 2018 GB 1.0 – Technical modifications and delivery rights reserved. Measurements, prices and illustrations are subject to change. Although we check our catalogue thoroughly, we cannot completely rule out the possibility of printing mistakes. The colour tones shown in the catalogue are non-binding. In the interest of product development and improvement we reserve the right to technically modify products.



### TOPOIL SURFACE KIT

PROTECTION OF  
WOOD SURFACES/  
INITIAL CARE/CLEANING/  
MAINTENANCE



## TOPOIL

Oil-wax coating – especially developed for wooden furniture surfaces and kitchen worktops!

- > Clear or transparent, satin or matt, for interior use
- > Highly recommended for furniture and kitchen worktops made of wood
- > TopOil makes the wood surface resistant to common household chemicals and stains, water-repellent and abrasion-resistant. It is resistant to saliva and perspiration, food safe as well as suitable for children's toys.
- > Number of coats: two coats on raw wood. For renovation works, normally one coat applied to a clean and dry surface is sufficient – without sanding!
- > Can sizes: 0.5 L
- > 1 litre covers approx. 24 m<sup>2</sup> with 1 coat.



Apply with:



3028 Clear Satin



3058 Clear Matt



3061 Acacia



3068 Natural

## SURFACE PREPARATION

- > Wood surface must be clean, dry and frost-free (moisture content max. 18%).
- > Osmo TopOil is ready to use. Do not thin. Shake well before use.
- > Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed. As a general rule, wear a dust mask during sanding works. Fill small cracks, larger joints or holes in wood (with Osmo Wood Filler).
- > Sand wood surfaces carefully. Begin with coarse sandpaper – final sanding work for furniture and worktops P150-240 (depending on wood species – for worktops max. P150). Before oiling the surface, remove sanding dust with a broom or vacuum cleaner.
- > The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.
- > Applying the product too generously and insufficient ventilation lead to delays in drying time.
- > On dark/reddish wood species, TopOil Natural is visible as slightly white chalky surface. A trial application is recommended.
- > Multi-purpose and other household cleaners and detergents are highly detrimental to the finished surface as discolouration or staining may be possible.



More information can be found on our website: [www.osmo.de/en](http://www.osmo.de/en)

## MANUAL PROCESSING

### Finished surface in 2 days, 2 coats

1. First coat on the raw, sanded wood approx. 25-35 ml/m<sup>2</sup>. Apply TopOil to the surface with an Osmo Microfibre Roller, Flat Brush or Oil Finish Applicator Fleece. Mistakes in the wet coating can be corrected up to 15 minutes after the first application.
2. Drying time approx. 8-10 hours (normal climatic conditions, 23 °C/50 % rel. humidity). Lower temperatures and/or higher humidity can increase drying time. Ventilate well.
3. Second coat approx. 5-10 ml/m<sup>2</sup>. Best to apply with an Osmo Oil Finish Applicator Fleece or a lint-free cloth.
4. Drying time approx. 8-10 hours; see point 2.
5. To avoid applying too much product, follow Point 3 for any maintenance coats.

## ADVANTAGES

- > Food safe according to EN 1186 part 5/14
- > Resistant to household chemicals and stains
- > Water-repellent and wear-resistant
- > Resistant to saliva and perspiration, suitable for children's toys
- > Safe for humans, animals and plants (when dry) according to DIN EN 71.3 and DIN 53160.